



Heckmann Building Products Inc.

1501 N. 31st Avenue

Melrose Park, IL 60160-2911

800-621-4140 or 708-865-2403 Fax: 708-865-2640

www.heckmannbuildingprods.com

SUBMITTAL SHEET: #234 SMALL STAY-PUT FLASHING REGLET

The stay-put flashing reglet is the most reliable way to terminate roofing, waterproofing, and flashing in concrete walls. Use at parapet walls and above shelf angles, lintels, and ledges.

Standard Size: 26 gage 1" and 1/2" flanges with 1/4" lips for adhering to concrete. Opening is 1/4" x 1-1/4" deep at a 65 degree angle into the wall. (Actual depth from face of concrete is 1".) Standard length is 10 feet. Available in Stainless Steel or Mill Galvanized Steel. Foam-fill is supplied to prevent concrete from entering the slot during the pour. (See product #231 Stay-Put Flashing Reglet for larger slot size)

Installation: Nail to inside face of concrete forms. Use double-headed nails to resist damage when forms are stripped. Roofing or flashing is typically secured in reglet with lead wedges, resilient rod stock, or sealants.

Stainless Steel:

Sheet metal anchors and ties: ASTM A 167 AISI Type 304.


Plate and bent bar anchors: ASTM A 666 AISI Type 304.

Wire ties and anchors: ASTM A 580 AISI Type 304.

Mill Galvanized:

Sheet metal anchors and ties: ASTM A 653 G60

Wire: ASTM A 641 (0.1 oz/ ft².)



234

Approvals:

Comments: