

## #106 Dovetail Corrugated Anchor Specification

### SECTION 04 00 00 MASONRY Section 04 05 19.16 Masonry Anchors Section 04 05 23 Masonry Accessories

#### **PART 1: GENERAL**

##### 1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

##### 1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

#### **PART 2: MANUFACTURER**

##### 2.1 MANUFACTURER

Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

##### 2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.

B. Stainless Steel AISI [Type 304] [or] [Type 316]

C. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.

D. ASTM A666-15 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.

##### 2.3 MATERIALS

*Select gauge, length and steel type*

**106 DOVETAIL CORRUGATED ANCHOR [gauge] x 1 inch (25 mm) wide  
x [length from face of concrete]  
[Type 304 Stainless Steel] or [Type 316 Stainless Steel]**

### **PART 3: EXECUTION**

A. Install as specified in applicable masonry section(s).

B. Anchors: Insert anchor at desired height into Dovetail Anchor Slot. Turn 90 degrees to lock into the slot. Place mortar above and below anchor in the mortar joint. **[Specify spacing of anchors].**