



**Standard Anchor Bolts**

**Special**

Dia -	1/2"		5/8"		3/4"		1"	
Length	Plain	HD	Plain	HD	Plain	HD	Plain	HD
10"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
12"			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
15"					<input type="checkbox"/>	<input type="checkbox"/>		
16"			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
18"			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
24"					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
30"						<input type="checkbox"/>		

**Material Specifications**

**Stainless Steel:** Sheet metal anchors and ties:

Rod: ASTM A 580 AISI Type 304

(AISI Type 316 available upon request)

**Hotdip Galvanized:** ASTM A 153 Class

B-2: (1.50 oz/ ft<sup>2</sup>)(0.46kg/m<sup>2</sup>)

**Plain Carbon Steel:**

Wire: ASTM A 82/A82M Tensile Strengths

80,000 psi Yield Point 70,000 psi

**Made to Order**

Diameter:  1/4 "  3/8"  1/2"  5/8"  3/4"

Overall Length (od): \_\_\_\_\_

Bend Length (od): \_\_\_\_\_

Thread Length: \_\_\_\_\_

Finish:  Stainless type 304  Hot Dip Galvanized

Plain Steel

Quantity: \_\_\_\_\_