

#187 Hole-Type Brick Veneer Anchor

SECTION 04 00 00 MASONRY  
Section 04 05 19.16 Masonry Anchors  
Section 04 05 23 Masonry Accessories

**PART 1: GENERAL**

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

**PART 2: MANUFACTURER**

2.1 MANUFACTURER

Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

2.2 APPLICATIONS

- A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-22.
- B. Stainless Steel AISI [Type 304] or [Type 316].
- C. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.
- D. ASTM A666-15 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.
- E. ASTM A153/A153M-16 Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware.

F. Zinc Alloy 710 for use as a firewall anchor (1/8" thick only).

## 2.3 MATERIALS

***Select the Following***

### **187 HOLE-TYPE BRICK VENEER ANCHOR**

**Standard:** 16 gauge x 1-1/4" wide with a 1-1/2" od bend with a centered 5/16" diameter hole. Length: [3-1/2"] [5-1/2"] Steel Type: [Type 304 Stainless Steel] [Hotdip Galvanized After Fabrication] [Zinc Alloy 710 for Firewall Applications]

**Custom:** (For custom sizes refer to product 340-A Corrugated L-Anchor with Hole)

## **PART 3: EXECUTION**

A. Install as specified in applicable masonry section(s).