

**Submittal Sheet**  
**#315-D Screw-On**  
**Anchor Plate**

Used as an adjustable anchor for attaching brick veneer to a solid backup wall of Concrete, CMU, ICF or steel or wood stud backup wall with Gypsum Sheathing or Plywood. This is not for use with polyiso insulation or mineral wool. Vertical adjustability is 4".



Shown With #316 Triangle  
 and #363 Plastic Seismic Clip

**Standards:**

Thickness:  12 gage     14 gage

Length: 5-1/2"    Width: 1 1/4"    Hole size 5/16"

Finish:  Stainless type 304     Hot Dip Galvanized

Quantity: \_\_\_\_\_

For Seismic requirements, see Heckmann product 363 Plastic Seismic Clip that attaches to the wire tie

**Material Specifications**

**Stainless Steel:** Sheet metal anchors and ties: ASTM A 167, ASTM A 666, ASTM A 240/A240M AISI Type 304.  
 Wire ties and anchors: ASTM A 580 AISI Type 304

**Plain Carbon Steel:** ASTM A1008/A1008M Structural Steel ASTM A36/A36M-08  
 Wire: ASTM A 82/A82M Tensile Strengths 80,000 psi Yield Point 70,000 psi

**Hotdip Galvanized:** ASTM A 153 Class B-2: (1.50 oz/ ft2.)(0.46kg/m2)