

#352 Rubber Expansion Joint

SECTION 04 00 00 MASONRY Section 04 05 23 Masonry Accessories Section 04 05 23.13 Masonry Control and Expansion Joints Section 04 21 13.13 Brick Veneer Masonry

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

B. ASTM D2000–18 Standard Classification System for Rubber Products in Automotive Applications

C. ASTM D2240-15e1 Standard Test Method for Rubber Property Durometer Hardness

2.3 MATERIALS

No. 352 RUBBER CONTROL JOINT

Standard: Thickness: 1/4" Depth: 02-5/8" [6-7/8'] [11-1/8"]

Tee: Thickness: 1/4" Depth 2-5/8"

Materials: Extruded Rubber

PART 3: EXECUTION

- A. Install as specified in applicable masonry section(s).
- B. Install vertically at expansion joints and seal interior and exterior joint with backer rod and sealant.