

Drill a 3/8" diameter hole into the backup 2" deep.

100 pcs per box  
 600 pcs per carton


**QUANTITY:** \_\_\_\_\_

**STANDARD:**

One Size: 3/8" diameter x 1-3/4" long.

**LOAD VALUES:**

Tension Loads: (1" embedment - ultimate loads) CMU block - cell 1,720 lbs  
 CMU block - rib 2,015 lbs  
 Brick - 1,550 lbs  
 Mortar Joint - 1,435 lbs  
 Concrete (3,000psi) - 1,785 lbs



**CLICK OR SCAN FOR MATERIAL SPECIFICATIONS**

**PROJECT DETAILS:**

LOCATION: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

**CONTACT INFO**

NAME: \_\_\_\_\_

COMPANY: \_\_\_\_\_

PHONE: \_\_\_\_\_

E-MAIL: \_\_\_\_\_

Heckmann is not responsible for your choice of anchors and dimensions for your project. The choice of anchors and products should be decided by the architects or engineers knowledgeable with the project. Once a custom order has been placed it cannot be canceled or returned. Any changes to the original order may require additional charges. Your signature is required for us to proceed. By signing this order, you agree that you have reviewed the details and specifications of the custom order and that said details and specifications are per your request. Further, by signing this order you are waiving any claim against or right of non-payment for products produced to the specifications of the order.

**DATE:** \_\_\_\_\_

**ACCEPTED BY:** \_\_\_\_\_