

SECTION 04 00 00 MASONRY

04 05 23.19 Masonry Cavity Drainage, Weepholes, and Vents

PART 1 GENERAL

1.1 RELATED SECTIONS

01 33 23 Provide shop drawings for all product locations.

1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data on each type of product furnished.

PART 2 PRODUCTS

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

- A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

2.3 MATERIALS

- A. **Cell Vent: No. 85**; One piece flexible extrusion made from UV-resistant polypropylene copolymer, full height and width of head joint and depth 1/8" less than depth of outer wythe, in color selected from manufacturer's standard.
[Regular: 3/8 inch wide x 2-1/2 inches high x 3-3/8 inches long] [Jumbo: 3/8 inch wide x 3-3/8 inches wide x 4 inches long]

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install as specified in applicable masonry section(s).